



Ramp Equipment Co
910-794-7189
Classic

Model HTA (3,000 lb to 6,000 lb Drawbar pull)



Standard Features

- F-N-R shifter
- Keyless anti-restart ignition switch
- Two Headlights
- Combination Tail/Stop Lights & Back-up Light
- Volt Meter
- Water Temperature Gauge
- Engine Oil Pressure Gauge
- Engine Hour Meter Gauge
- Fuel Level Gauge
- Standard driver and passenger seat

Specifications subject to improvement and/or change without notice

Harlan Global Manufacturing, LLC
27 Stanley Road * Kansas City, Kansas 66115 * USA
913-342-5650 * 800-255-4262 * Fax 913-321-5802
www.harlan-corp.com

Specifications for Model: Classic (3k-6k) Towing

Drawbar Pull Available

Model	DBP	(+/-)GVW	(+/-) Towed Wt
HTA30	3,000 lbs	4,000 lbs	30,000 lbs
HTA40	4,000 lbs	5,250 lbs	40,000 lbs
HTA50	5,000 lbs	6,500 lbs	50,000 lbs
HTA60	6,000 lbs	7,200 lbs	60,000 lbs

Towed weight on a dry surface up to a 3% grade

Dimensions

Length	112" (2845 mm)
Width	55.5" (1410 mm)
Height	63" (1600 mm)
Height w/cab	84" (2134 mm)
Wheel Base	70" (1778 mm)
Ground Clearance	6" (152 mm)

- Available Diesel Engines
Equipped with Gauge & Sender system
- **Cummins**
 - **Perkins**
 - **Deutz**
- Available Gasoline
(3k – 5k only)
- **GM**

- Drive Axle**
- Heavy duty Harlan—10,000 lb Load Capacity
- Steer Axle**
- Heavy duty Harlan with 1 1/8" King Pin
- Suspension**
- Leaf Springs on front and rear axles
- Brakes**
- Service:**
- Dual Split System
 - Hydraulic/Hydraulic
 - Dual rear disc w/optional front disc brakes
 - Other brake options available upon request
- Parking:**
- Mechanical Drum (lever activated)
- Towing Coupler**
- E-Hitch – 1" Pin
 - Other couplers available on request

- Transmission**
- Ford C-6 Automatic
 - 3-speeds forward, 1 reverse
- Electrical**
- 12 V, Negative ground
- Cooling System**
- Liquid cooled 8.5 quart capacity radiator with integral transmission cooler
 - Oil cooled radiator with the Deutz engine
- Steering System:**
- Hydraulic Steering (Saginaw power assisted)
- Turning Radius**
- 135" (3429mm)

- Tires**
- Front: 6.50 x 10
 - Rear: LT215/80R x16